

Information requirements for electric local space heaters

Model identifier(s): TIH 400 S

| Item | Symbol | Value | Unit | Item | Unit |
|--|---|-------|------|---|------|
| Heat output | | | | Type of heat input, for electric storage local space heaters only (select one) | |
| Nominal heat output | P_{nom} | 0.4 | kW | manual heat charge control, with integrated thermostat | NA |
| Minimum heat output (indicative) | P_{min} | NA | kW | manual heat charge control with room and/or outdoor temperature feedback | NA |
| Maximum continuous heat output | $P_{max,c}$ | 0.4 | kW | electronic heat charge control with room and/or outdoor temperature feedback | NA |
| Auxiliary electricity consumption | | | | fan assisted heat output | |
| At nominal heat output | el_{max} | 0.418 | kW | Type of heat output/room temperature control (select one) | |
| At minimum heat output | el_{min} | NA | kW | single stage heat output and no room temperature control | NO |
| In standby mode | el_{SB} | NA | kW | Two or more manual stages, no room temperature control | NO |
| | | | | with mechanic thermostat room temperature control | NO |
| | | | | with electronic room temperature control | NO |
| | | | | electronic room temperature control plus day timer | NO |
| | | | | electronic room temperature control plus week timer | YES |
| | | | | Other control options (multiple selections possible) | |
| | | | | room temperature control, with presence detection | NO |
| | | | | room temperature control, with open window detection | NO |
| | | | | with distance control option | NO |
| | | | | with adaptive start control | YES |
| | | | | with working time limitation | NO |
| | | | | with black bulb sensor | NO |
| Contact details | Trotec GmbH & Co. KG · Grebbener Str. 7 · 52525 Heinsberg · Germany | | | | |