

Supplier TOSHIBA CARRIER CORPORATION

Unutarnja jedinica RAS-B07J2KVG-E

Vanjska jedinica RAS-07J2AVG-E

### Sound power level

Unutarnja jedinica (hlađenje) dB 53

Vanjska jedinica (hlađenje) dB 61

Unutarnja jedinica (grijanje) dB 53

Vanjska jedinica (grijanje) dB 63

### Radni medij

Tip R32

Potencijal globalnog zatopljenja kgCO<sub>2</sub>eq 675

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO<sub>2</sub>, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

### Cooling

Energy efficiency class A++

Design load (P<sub>designc</sub>) kW 2.0

Seasonal efficiency (SEER) 6.10

Sezonska snaga električnog priključka (Q<sub>CE</sub>) kWh/annum 115

## Heating

		Heating/Average	Heating/Warmer	Heating/Colder
Energy efficiency class		A+	A+	x
Design load (Pdesignh)	kW	2.0	1.1	x,x
Seasonal efficiency (SCOP)		4.00	4.30	x,xx
Sezonska snaga električnog priključka (Q <sub>HE</sub> )	kWh/annum	699	354	x
Pričuvni kapacitet grijanja	kW	0.00		
<b>Navedeni kapacitet grijanja pri sobnoj temperaturi od 20° C i vanjskoj temperaturi zraka (Tj)</b>				
Tj= -7°C (Pdh)	kW	1.77	-	x,xx
Tj= 2°C (Pdh)	kW	1.08	1.08	x,xx
Tj= 7°C (Pdh)	kW	0.69	0.69	x,xx
Tj= 12°C (Pdh)	kW	0.68	0.68	x,xx
Tj=bivalent temperature (Pdh)	kW	1.77	1.08	x,xx
Tj=granična radna temperatura (Pdh)	kW	2.68	2.68	x,xx
Tj= -15°C (Pdh)	kW	-	-	x,xx