

## Split klima uređaj

Outdoor unit	Single inverter	RAS-10J2AVG-E
Indoor unit	SEIYA R32	RAS-B10J2KVG-E

Function		Design load		Seasonal efficiency
Cooling	Y	Cooling	Pdesignc	2.5 kW
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	2.4 kW
Grijanje - toplice	Y	Heating/Warmer	Pdesignh	1.3 kW
Grijanje - hladnije	N	Upravljanje kapacitetom = Varijabilno		

## Cooling

### Capacity

Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature T<sub>j</sub>.

### Učinkovitost

Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature T<sub>j</sub>.

T <sub>j</sub> =35°C	Pdc	2.50 kW	T <sub>j</sub> =35°C	EERd	3.25
T <sub>j</sub> =30°C	Pdc	1.84 kW	T <sub>j</sub> =30°C	EERd	4.85
T <sub>j</sub> =25°C	Pdc	1.18 kW	T <sub>j</sub> =25°C	EERd	7.90
T <sub>j</sub> =20°C	Pdc	0.93 kW	T <sub>j</sub> =20°C	EERd	9.75

## Grijanje (prosječna klimatska zona)

### Capacity

Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature T<sub>j</sub>.

### Učinkovitost

Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature T<sub>j</sub>.

T <sub>j</sub> =-7°C	Pdh	2.12 kW	T <sub>j</sub> =-7°C	COPd	2.60
T <sub>j</sub> =2°C	Pdh	1.29 kW	T <sub>j</sub> =2°C	COPd	4.15
T <sub>j</sub> =7°C	Pdh	0.83 kW	T <sub>j</sub> =7°C	COPd	4.95
T <sub>j</sub> =12°C	Pdh	0.78 kW	T <sub>j</sub> =12°C	COPd	5.67
T <sub>j</sub> =bivalent temperature	Pdh	2.12 kW	T <sub>j</sub> =bivalent temperature	COPd	2.60
T <sub>j</sub> =granična radna temperatura	Pdh	1.72 kW	T <sub>j</sub> =granična radna temperatura	COPd	2.20
Bivalentna temperatura		-7 °C			
Granične radne temperature		-15 °C			

## Heating (Warmer climate)

### Capacity

Declared capacity for Heating/Warmer at indoor temperature 20°C and outdoor temperature Tj.

### Učinkovitost

Declared coefficient of performance for Heating/Warmer climate at indoor temperature 20°C and outdoor temperature Tj.

Tj=2°C	Pdh	1.29	kW	Tj=2°C	COPd	4.15
Tj=7°C	Pdh	0.83	kW	Tj=7°C	COPd	4.95
Tj=12°C	Pdh	0.78	kW	Tj=12°C	COPd	5.67
Tj=bivalent temperature	Pdh	1.29	kW	Tj=bivalent temperature	COPd	4.15
Tj=granična radna temperatura	Pdh	1.72	kW	Tj=granična radna temperatura	COPd	2.20
Bivalentna temperatura	Tbiv	X	°C			
Granične radne temperature	Tol	X	°C			

## Electricity

### Electric power input in power modes other than "on mode"

### Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.001	kW	Cooling	QCE	143	kWh/a
Stanje mirovanja	Psb	0.001	kW	Heating/Average	QHE/A	839	kWh/a
Stanje isključenosti termostata	Pto	0.029	kW	Heating/Warmer	QHE/B	393	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

## Radni medij

Tip	R32				
Težina		0.43	kg		
Potencijal globalnog zatopljenja	GWP		675	kgCO <sub>2</sub> eq.	

## Sound power level - db(A)

## Rated air flow - m<sup>3</sup>/h

	Cooling	Heating		Cooling	Heating
RAS-10J2AVG-E	63	65	RAS-10J2AVG-E	1800	1800
RAS-B10J2KVG-E	54	54	RAS-B10J2KVG-E	540	552

## Dimenzije

	Visina	Širina	Dubina	Težina
RAS-10J2AVG-E	550 mm	660 mm	240 mm	23 kg
RAS-B10J2KVG-E	293 mm	798 mm	230 mm	9 kg

Uvoznik / distributer u EU:  
Toshiba Carrier UK Ltd.  
Kontakt partner za dobivanje više informacija  
Porsham Close, Belliver Industrial Estate,  
PLYMOUTH, Devon, PL6 7DB.  
United Kingdom

---