

Split klima uređaj

Outdoor unit	Single inverter	RAS-13J2AVG-E
Indoor unit	SEIYA R32	RAS-B13J2KVG-E

Function		Design load			Seasonal efficiency			
Cooling	Y	Cooling	Pdesignc	3.3 kW	Cooling	SEER	6.10	A++
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	2.8 kW	Heating/Average	SCOP(A)	4.00	A+
Grijanje - toplije	Y	Heating/Warmer	Pdesignh	1.5 kW	Heating/Warmer	SCOP(W)	x,xx	x
Grijanje - hladnije	N	Upravljanje kapacitetom = Varijabilno						

Cooling

Capacity				Učinkovitost		
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.				Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.		
Tj=35°C	Pdc	3.30 kW		Tj=35°C	EERd	3.00
Tj=30°C	Pdc	2.43 kW		Tj=30°C	EERd	4.75
Tj=25°C	Pdc	1.56 kW		Tj=25°C	EERd	7.60
Tj=20°C	Pdc	1.04 kW		Tj=20°C	EERd	10.40

Grijanje (prosječna klimatska zona)

Capacity				Učinkovitost		
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.		
Tj=-7°C	Pdh	2.48 kW		Tj=-7°C	COPd	2.65
Tj=2°C	Pdh	1.51 kW		Tj=2°C	COPd	3.95
Tj=7°C	Pdh	0.97 kW		Tj=7°C	COPd	5.30
Tj=12°C	Pdh	0.84 kW		Tj=12°C	COPd	5.90
Tj=bivalent temperature	Pdh	2.48 kW		Tj=bivalent temperature	COPd	2.65
Tj=granična radna temperatura	Pdh	1.89 kW		Tj=granična radna temperatura	COPd	2.20
Bivalentna temperatura		-7 °C				
Granične radne temperature		-15 °C				

Heating (Warmer climate)

Capacity				Učinkovitost		
Declared capacity for Heating/Warmer at indoor temperature 20°C and outdoor temperature Tj.				Declared coefficient of performance for Heating/Warmer climate at indoor temperature 20°C and outdoor temperature Tj.		
Tj=2°C	Pdh	1.51	kW	Tj=2°C	COPd	3.9E
Tj=7°C	Pdh	0.97	kW	Tj=7°C	COPd	5.3C
Tj=12°C	Pdh	0.84	kW	Tj=12°C	COPd	5.9C
Tj=bivalent temperature	Pdh	1.51	kW	Tj=bivalent temperature	COPd	3.9E
Tj=granična radna temperatura	Pdh	1.89	kW	Tj=granična radna temperatura	COPd	2.2C
Bivalentna temperatura		Tbiv	X	°C		
Granične radne temperature		Tol	X	°C		

Electricity

Electric power input in power modes other than "on mode"				Sezonska snaga električnog priključka		
Stanje isključenosti	Poff	0.001	kW	Cooling	QCE	189 kWh/a
Stanje mirovanja	Psb	0.001	kW	Heating/Average	QHE/A	980 kWh/a
Stanje isključenosti termostata	Pto	0.031	kW	Heating/Warmer	QHE/B	435 kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x kWh/a

Radni medij

Tip	R32				
Težina	0.46 kg				
Potencijal globalnog zatopljenja	GWP	675 kgCO ₂ eq.			

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAS-13J2AVG-E	63	65	RAS-13J2AVG-E	1980	1980
RAS-B13J2KVG-E	56	57	RAS-B13J2KVG-E	600	618

Dimenzije

	Visina	Širina	Dubina	Težina
RAS-13J2AVG-E	530 mm	660 mm	240 mm	24 kg
RAS-B13J2KVG-E	293 mm	798 mm	230 mm	9 kg

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:
Toshiba Carrier UK Ltd.
Porsham Close, Belliver Industrial Estate,
PLYMOUTH, Devon, PL6 7DB.
United Kingdom
