

Split klima uređaj

Outdoor unit	Single inverter	RAV-GM1401ATP-E
Indoor unit	4-way Cassette	RAV-RM1401UTP-E

Function		Design load			Seasonal efficiency		
Cooling	Y	Cooling	Pdesignc	12.0 kW	Cooling	SEER	5.71 A+
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	8.0 kW	Heating/Average	SCOP(A)	4.29 A+
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno					
Grijanje - hladnije	N						

Cooling

Capacity				Učinkovitost		
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.				Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.		
Tj=35°C	Pdc	12.00 kW		Tj=35°C	EERd	2.80
Tj=30°C	Pdc	8.84 kW		Tj=30°C	EERd	4.54
Tj=25°C	Pdc	5.68 kW		Tj=25°C	EERd	6.84
Tj=20°C	Pdc	4.53 kW		Tj=20°C	EERd	11.92

Grijanje (prosječna klimatska zona)

Capacity				Učinkovitost		
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.		
Tj=-7°C	Pdh	7.08 kW		Tj=-7°C	COPd	2.74
Tj=2°C	Pdh	4.31 kW		Tj=2°C	COPd	4.37
Tj=7°C	Pdh	2.91 kW		Tj=7°C	COPd	5.53
Tj=12°C	Pdh	3.40 kW		Tj=12°C	COPd	6.52
Tj=bivalent temperature	Pdh	7.08 kW		Tj=bivalent temperature	COPd	2.74
Tj=granična radna temperatura	Pdh	5.72 kW		Tj=granična radna temperatura	COPd	1.80
Bivalentna temperatura		-7 °C				
Granične radne temperature		-15 °C				

Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.016	kW	Cooling	QCE	736	kWh/a
Stanje mirovanja	Psb	0.016	kW	Heating/Average	QHE/A	2611	kWh/a
Stanje isključenosti termostata	Pto	0.083	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Radni medij

Tip	R32		
Težina	2.10 kg		
Potencijal globalnog zatopljenja	GWP	675 kgCO ₂ eq.	

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAV-GM1401ATP-E	70	74	RAV-GM1401ATP-E	4200	4200
RAV-RM1401UTP-E	59	59	RAV-RM1401UTP-E	2100	2100

Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GM1401ATP-E	890 mm	900 mm	320 mm	68 kg
RAV-RM1401UTP-E	319 mm	840 mm	840 mm	24 kg

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:
Toshiba Carrier UK Ltd.
Porsham Close, Belliver Industrial Estate,
PLYMOUTH, Devon, PL6 7DB.
United Kingdom