

Split klima uređaj

Outdoor unit	Single inverter	RAV-GM1401AT8P-E
Indoor unit	4-way Cassette	RAV-RM1401UTP-E

Function		Design load			Seasonal efficiency			
Cooling	Y	Cooling	P _{designc}	12.0 kW	Cooling	SEER	5.71	A+
Grijanje - u prosjeku	Y	Heating/Average	P _{designh}	8.0 kW	Heating/Average	SCOP(A)	4.29	A+
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

Cooling

Capacity				Učinkovitost		
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature T _j .				Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature T _j .		
T _j =35°C	P _{dc}	12.00	kW	T _j =35°C	EERd	2.80
T _j =30°C	P _{dc}	8.84	kW	T _j =30°C	EERd	4.54
T _j =25°C	P _{dc}	5.68	kW	T _j =25°C	EERd	6.84
T _j =20°C	P _{dc}	4.53	kW	T _j =20°C	EERd	11.92

Grijanje (prosječna klimatska zona)

Capacity				Učinkovitost		
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature T _j .				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature T _j .		
T _j =-7°C	P _{dh}	7.08	kW	T _j =-7°C	COPd	2.74
T _j =2°C	P _{dh}	4.31	kW	T _j =2°C	COPd	4.37
T _j =7°C	P _{dh}	2.91	kW	T _j =7°C	COPd	5.53
T _j =12°C	P _{dh}	3.40	kW	T _j =12°C	COPd	6.52
T _j =bivalent temperature	P _{dh}	7.08	kW	T _j =bivalent temperature	COPd	2.74
T _j =granična radna temperatura	P _{dh}	5.72	kW	T _j =granična radna temperatura	COPd	1.80
Bivalentna temperatura		-7	°C			
Granične radne temperature		-15	°C			

Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.016	kW	Cooling	QCE	736	kWh/a
Stanje mirovanja	Psb	0.016	kW	Heating/Average	QHE/A	2611	kWh/a
Stanje isključenosti termostata	Pto	0.083	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Radni medij

Tip	R32		
Težina	2.10 kg		
Potencijal globalnog zatopljenja	GWP	675 kgCO ₂ eq.	

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAV-GM1401AT8P-E	70	74	RAV-GM1401AT8P-E	4200	4200
RAV-RM1401UTP-E	59	59	RAV-RM1401UTP-E	2100	2100

Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GM1401AT8P-E	890 mm	900 mm	320 mm	68 kg
RAV-RM1401UTP-E	319 mm	840 mm	840 mm	24 kg

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:
Toshiba Carrier UK Ltd.
Porsham Close, Belliver Industrial Estate,
PLYMOUTH, Devon, PL6 7DB.
United Kingdom