

Split klima uređaj

| | | |
|--------------|------------------------------------|-----------------|
| Outdoor unit | Single inverter | RAV-GM301ATP-E |
| Indoor unit | Hi-wall Bi Refrigerant - R32 R410A | RAV-RM301KRTP-E |

| Function | | Design load | | | Seasonal efficiency | | | |
|-----------------------|---|---------------------------------------|----------|--------|---------------------|---------|------|-----|
| Cooling | Y | Cooling | Pdesignc | 2.5 kW | Cooling | SEER | 6.36 | A++ |
| Grijanje - u prosjeku | Y | Heating/Average | Pdesignh | 2.6 kW | Heating/Average | SCOP(A) | 4.10 | A+ |
| Grijanje - toplije | N | Upravljanje kapacitetom = Varijabilno | | | | | | |
| Grijanje - hladnije | N | | | | | | | |

Cooling

| Capacity | | | Učinkovitost | | |
|--|-----|---------|---|------|-------|
| Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj. | | | Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj. | | |
| Tj=35°C | Pdc | 2.50 kW | Tj=35°C | EERd | 4.10 |
| Tj=30°C | Pdc | 1.84 kW | Tj=30°C | EERd | 5.55 |
| Tj=25°C | Pdc | 1.18 kW | Tj=25°C | EERd | 9.05 |
| Tj=20°C | Pdc | 1.09 kW | Tj=20°C | EERd | 12.70 |

Grijanje (prosječna klimatska zona)

| Capacity | | | Učinkovitost | | |
|--|-----|---------|--|------|------|
| Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj. | | | Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj. | | |
| Tj=-7°C | Pdh | 2.30 kW | Tj=-7°C | COPd | 2.83 |
| Tj=2°C | Pdh | 1.40 kW | Tj=2°C | COPd | 4.05 |
| Tj=7°C | Pdh | 0.90 kW | Tj=7°C | COPd | 5.11 |
| Tj=12°C | Pdh | 0.99 kW | Tj=12°C | COPd | 7.02 |
| Tj=bivalent temperature | Pdh | 2.30 kW | Tj=bivalent temperature | COPd | 2.83 |
| Tj=granična radna temperatura | Pdh | 1.38 kW | Tj=granična radna temperatura | COPd | 2.11 |
| Bivalentna temperatura | | -7 °C | | | |
| Granične radne temperature | | -15 °C | | | |

Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

| | | | | | | | |
|---------------------------------|------|-------|----|-----------------|-------|-----|-------|
| Stanje isključenosti | Poff | 0.009 | kW | Cooling | QCE | 138 | kWh/a |
| Stanje mirovanja | Psb | 0.009 | kW | Heating/Average | QHE/A | 887 | kWh/a |
| Stanje isključenosti termostata | Pto | 0.020 | kW | Heating/Warmer | QHE/B | x | kWh/a |
| Način rada s grijačem kućišta | Pck | 0.000 | kW | Heating/Colder | QHE/C | x | kWh/a |

Radni medij

| | | | |
|----------------------------------|---------|---------------------------|--|
| Tip | R32 | | |
| Težina | 0.63 kg | | |
| Potencijal globalnog zatopljenja | GWP | 675 kgCO ₂ eq. | |

Sound power level - db(A)

Rated air flow - m³/h

| | Cooling | Heating | | Cooling | Heating |
|-----------------|---------|---------|-----------------|---------|---------|
| RAV-GM301ATP-E | 61 | 62 | RAV-GM301ATP-E | 1800 | 1800 |
| RAV-RM301KRTP-E | 55 | 55 | RAV-RM301KRTP-E | 670 | 670 |

Dimenzije

| | Visina | Širina | Dubina | Težina |
|-----------------|--------|--------|--------|--------|
| RAV-GM301ATP-E | 550 mm | 780 mm | 290 mm | 29 kg |
| RAV-RM301KRTP-E | 293 mm | 798 mm | 290 mm | 10 kg |

Harmonizirana norma EN14511:2007, EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:
Toshiba Carrier UK Ltd.
Porsham Close, Belliver Industrial Estate,
PLYMOUTH, Devon, PL6 7DB.
United Kingdom