

Split klima uređaj

Outdoor unit	Single inverter	RAV-GM401ATP-E
Indoor unit	Ceiling	RAV-RM401CTP-E

Function		Design load			Seasonal efficiency			
Cooling	Y	Cooling	Pdesignc	3.6 kW	Cooling	SEER	6.34	A++
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	2.7 kW	Heating/Average	SCOP(A)	5.10	A+++
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

Cooling

Capacity				Učinkovitost		
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.				Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.		
Tj=35°C	Pdc	3.60 kW		Tj=35°C	EERd	4.34
Tj=30°C	Pdc	2.65 kW		Tj=30°C	EERd	6.22
Tj=25°C	Pdc	1.71 kW		Tj=25°C	EERd	8.48
Tj=20°C	Pdc	1.39 kW		Tj=20°C	EERd	11.06

Grijanje (prosječna klimatska zona)

Capacity				Učinkovitost		
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.		
Tj=-7°C	Pdh	2.39 kW		Tj=-7°C	COPd	3.21
Tj=2°C	Pdh	1.45 kW		Tj=2°C	COPd	5.29
Tj=7°C	Pdh	1.18 kW		Tj=7°C	COPd	6.90
Tj=12°C	Pdh	1.30 kW		Tj=12°C	COPd	7.45
Tj=bivalent temperature	Pdh	2.39 kW		Tj=bivalent temperature	COPd	3.21
Tj=granična radna temperatura	Pdh	2.60 kW		Tj=granična radna temperatura	COPd	2.00
Bivalentna temperatura		-7 °C				
Granične radne temperature		-15 °C				

Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.012	kW	Cooling	QCE	199	kWh/a
Stanje mirovanja	Psb	0.012	kW	Heating/Average	QHE/A	741	kWh/a
Stanje isključenosti termostata	Pto	0.033	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Radni medij

Tip	R32		
Težina	0.90 kg		
Potencijal globalnog zatopljenja	GWP	675 kgCO ₂ eq.	

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAV-GM401ATP-E	64	65	RAV-GM401ATP-E	2200	2200
RAV-RM401CTP-E	52	52	RAV-RM401CTP-E	900	900

Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GM401ATP-E	550 mm	780 mm	290 mm	34 kg
RAV-RM401CTP-E	235 mm	952 mm	690 mm	23 kg

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:
Toshiba Carrier UK Ltd.
Porsham Close, Belliver Industrial Estate,
PLYMOUTH, Devon, PL6 7DB.
United Kingdom