

## Split klima uređaj

Outdoor unit	Single inverter	RAV-GM1101ATP-E
Indoor unit	Standard Duct	RAV-RM1101BTP-E

Function		Design load			Seasonal efficiency			
Cooling	Y	Cooling	Pdesignc	9.5 kW	Cooling	SEER	5.28	A
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	7.6 kW	Heating/Average	SCOP(A)	4.19	A+
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

## Cooling

Capacity				Učinkovitost			
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.				Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.			
Tj=35°C	Pdc	9.50 kW		Tj=35°C	EERd		3.18
Tj=30°C	Pdc	7.00 kW		Tj=30°C	EERd		4.83
Tj=25°C	Pdc	4.50 kW		Tj=25°C	EERd		6.38
Tj=20°C	Pdc	4.00 kW		Tj=20°C	EERd		10.65

## Grijanje (prosječna klimatska zona)

Capacity				Učinkovitost			
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.			
Tj=-7°C	Pdh	6.72 kW		Tj=-7°C	COPd		2.69
Tj=2°C	Pdh	4.31 kW		Tj=2°C	COPd		4.29
Tj=7°C	Pdh	2.85 kW		Tj=7°C	COPd		5.52
Tj=12°C	Pdh	3.10 kW		Tj=12°C	COPd		6.60
Tj=bivalent temperature	Pdh	6.72 kW		Tj=bivalent temperature	COPd		2.69
Tj=granična radna temperatura	Pdh	4.57 kW		Tj=granična radna temperatura	COPd		1.58
Bivalentna temperatura		-7 °C					
Granične radne temperature		-15 °C					

## Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.016	kW	Cooling	QCE	629	kWh/a
Stanje mirovanja	Psb	0.016	kW	Heating/Average	QHE/A	2537	kWh/a
Stanje isključenosti termostata	Pto	0.203	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

## Radni medij

Tip	R32		
Težina	2.10 kg		
Potencijal globalnog zatopljenja	GWP	675 kgCO <sub>2</sub> eq.	

## Sound power level - db(A)

## Rated air flow - m<sup>3</sup>/h

	Cooling	Heating		Cooling	Heating
RAV-GM1101ATP-E	70	74	RAV-GM1101ATP-E	4080	4080
RAV-RM1101BTP-E	55	55	RAV-RM1101BTP-E	2100	2100

## Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GM1101ATP-E	890 mm	900 mm	320 mm	68 kg
RAV-RM1101BTP-E	275 mm	1400 mm	750 mm	40 kg

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:  
Toshiba Carrier UK Ltd.  
Porsham Close, Belliver Industrial Estate,  
PLYMOUTH, Devon, PL6 7DB.  
United Kingdom