

Split klima uređaj

Outdoor unit	Single inverter	RAV-GM561ATP-E
Indoor unit	Compact 4-way Cassette	RAV-RM561MUT-E

Function		Design load			Seasonal efficiency			
Cooling	Y	Cooling	Pdesignc	5.0 kW	Cooling	SEER	5.69	A+
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	2.8 kW	Heating/Average	SCOP(A)	4.37	A+
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

Cooling

Capacity				Učinkovitost			
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.				Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.			
Tj=35°C	Pdc	5.00	kW	Tj=35°C	EERd		3.03
Tj=30°C	Pdc	3.68	kW	Tj=30°C	EERd		4.55
Tj=25°C	Pdc	2.37	kW	Tj=25°C	EERd		7.67
Tj=20°C	Pdc	1.67	kW	Tj=20°C	EERd		11.49

Grijanje (prosječna klimatska zona)

Capacity				Učinkovitost			
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.			
Tj=-7°C	Pdh	2.48	kW	Tj=-7°C	COPd		2.71
Tj=2°C	Pdh	1.51	kW	Tj=2°C	COPd		4.40
Tj=7°C	Pdh	0.97	kW	Tj=7°C	COPd		5.81
Tj=12°C	Pdh	0.95	kW	Tj=12°C	COPd		6.65
Tj=bivalent temperature	Pdh	2.48	kW	Tj=bivalent temperature	COPd		2.71
Tj=granična radna temperatura	Pdh	3.29	kW	Tj=granična radna temperatura	COPd		2.17
Bivalentna temperatura		-7	°C				
Granične radne temperature		-15	°C				

Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.012	kW	Cooling	QCE	307	kWh/a
Stanje mirovanja	Psb	0.012	kW	Heating/Average	QHE/A	897	kWh/a
Stanje isključenosti termostata	Pto	0.051	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Radni medij

Tip	R32		
Težina	0.90 kg		
Potencijal globalnog zatopljenja	GWP	675 kgCO ₂ eq.	

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAV-GM561ATP-E	63	65	RAV-GM561ATP-E	2400	2400
RAV-RM561MUT-E	47	47	RAV-RM561MUT-E	1050	1050

Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GM561ATP-E	550 mm	780 mm	290 mm	40 kg
RAV-RM561MUT-E	256 mm	575 mm	575 mm	15 kg

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:
Toshiba Carrier UK Ltd.
Porsham Close, Belliver Industrial Estate,
PLYMOUTH, Devon, PL6 7DB.
United Kingdom