

Split klima uređaj

Outdoor unit	Single inverter	RAV-GM801ATP-E
Indoor unit	Standard Duct	RAV-RM801BTP-E

Function

Design load

Seasonal efficiency

Cooling	Y	Cooling	Pdesignc	6.7 kW	Cooling	SEER	5.20	A
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	5.1 kW	Heating/Average	SCOP(A)	4.13	A+
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

Cooling

Capacity

Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

Učinkovitost

Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

Tj=35°C	Pdc	6.70 kW	Tj=35°C	EERd	2.82
Tj=30°C	Pdc	4.94 kW	Tj=30°C	EERd	4.41
Tj=25°C	Pdc	3.17 kW	Tj=25°C	EERd	5.81
Tj=20°C	Pdc	1.30 kW	Tj=20°C	EERd	10.22

Grijanje (prosječna klimatska zona)

Capacity

Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.

Učinkovitost

Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.

Tj=-7°C	Pdh	4.51 kW	Tj=-7°C	COPd	2.25
Tj=2°C	Pdh	2.75 kW	Tj=2°C	COPd	4.24
Tj=7°C	Pdh	1.77 kW	Tj=7°C	COPd	5.73
Tj=12°C	Pdh	1.11 kW	Tj=12°C	COPd	6.44
Tj=bivalent temperature	Pdh	4.51 kW	Tj=bivalent temperature	COPd	2.25
Tj=granična radna temperatura	Pdh	3.31 kW	Tj=granična radna temperatura	COPd	2.11
Bivalentna temperatura		-7 °C			
Granične radne temperature		-15 °C			

Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.012	kW	Cooling	QCE	451	kWh/a
Stanje mirovanja	Psb	0.012	kW	Heating/Average	QHE/A	1728	kWh/a
Stanje isključenosti termostata	Pto	0.060	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Radni medij

Tip	R32		
Težina	1.30 kg		
Potencijal globalnog zatopljenja	GWP	675 kgCO ₂ eq.	

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAV-GM801ATP-E	65	69	RAV-GM801ATP-E	2700	2700
RAV-RM801BTP-E	49	49	RAV-RM801BTP-E	1200	1200

Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GM801ATP-E	550 mm	780 mm	290 mm	42 kg
RAV-RM801BTP-E	275 mm	1000 mm	750 mm	30 kg

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:
Toshiba Carrier UK Ltd.
Porsham Close, Belliver Industrial Estate,
PLYMOUTH, Devon, PL6 7DB.
United Kingdom