

Split klima uređaj

Outdoor unit	Single inverter	RAV-GM801ATP-E
Indoor unit	Hi-wall Bi Refrigerant - R32 R410A	RAV-RM801KRTP-E

Function		Design load			Seasonal efficiency			
Cooling	Y	Cooling	Pdesignc	6.7 kW	Cooling	SEER	5.73	A+
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	5.1 kW	Heating/Average	SCOP(A)	4.01	A+
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

Cooling

Capacity			Učinkovitost		
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.			Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.		
Tj=35°C	Pdc	6.70 kW	Tj=35°C	EERd	2.75
Tj=30°C	Pdc	4.94 kW	Tj=30°C	EERd	4.41
Tj=25°C	Pdc	3.17 kW	Tj=25°C	EERd	7.31
Tj=20°C	Pdc	1.59 kW	Tj=20°C	EERd	10.20

Grijanje (prosječna klimatska zona)

Capacity			Učinkovitost		
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.			Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.		
Tj=-7°C	Pdh	4.51 kW	Tj=-7°C	COPd	2.49
Tj=2°C	Pdh	2.75 kW	Tj=2°C	COPd	3.76
Tj=7°C	Pdh	1.77 kW	Tj=7°C	COPd	6.00
Tj=12°C	Pdh	1.53 kW	Tj=12°C	COPd	6.86
Tj=bivalent temperature	Pdh	4.51 kW	Tj=bivalent temperature	COPd	2.49
Tj=granična radna temperatura	Pdh	3.12 kW	Tj=granična radna temperatura	COPd	1.82
Bivalentna temperatura		-7 °C			
Granične radne temperature		-15 °C			

Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.009	kW	Cooling	QCE	409	kWh/a
Stanje mirovanja	Psb	0.009	kW	Heating/Average	QHE/A	1780	kWh/a
Stanje isključenosti termostata	Pto	0.040	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Radni medij

Tip	R32		
Težina	1.30		kg
Potencijal globalnog zatopljenja	GWP	675	kgCO ₂ eq.

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAV-GM801ATP-E	63	65	RAV-GM801ATP-E	2400	2400
RAV-RM801KRTP-E	60	60	RAV-RM801KRTP-E	1040	1040

Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GM801ATP-E	550 mm	780 mm	290 mm	43 kg
RAV-RM801KRTP-E	320 mm	1050 mm	250 mm	14 kg

Harmonizirana norma	EN14511:2007, EN12102
---------------------	-----------------------

Metode obračuna - mjerne norme	PrEN 14825: 2011 Sekcija 8 i 9
--------------------------------	--------------------------------

Kontakt partner za dobivanje više informacija	Uvoznik / distributer u EU: Toshiba Carrier UK Ltd. Porsham Close, Belliver Industrial Estate, PLYMOUTH, Devon, PL6 7DB. United Kingdom
---	---