

Split klima uređaj

Outdoor unit	Single inverter	RAV-GP801AT-E
Indoor unit	4-WAY SMART CASSETTE	RAV-GM801UT-E

Function		Design load			Seasonal efficiency			
Cooling	Y	Cooling	Pdesignc	7.1 kW	Cooling	SEER	9.40	A++
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	5.1 kW	Heating/Average	SCOP(A)	5.51	A++
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

Cooling

Capacity

Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

Učinkovitost

Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

Tj=35°C	Pdc	7.10 kW	Tj=35°C	EERd	5.18
Tj=30°C	Pdc	5.37 kW	Tj=30°C	EERd	7.56
Tj=25°C	Pdc	3.35 kW	Tj=25°C	EERd	12.41
Tj=20°C	Pdc	2.25 kW	Tj=20°C	EERd	17.31

Grijanje (prosječna klimatska zona)

Capacity

Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.

Učinkovitost

Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.

Tj=-7°C	Pdh	4.51 kW	Tj=-7°C	COPd	3.61
Tj=2°C	Pdh	2.68 kW	Tj=2°C	COPd	5.58
Tj=7°C	Pdh	1.75 kW	Tj=7°C	COPd	7.00
Tj=12°C	Pdh	1.89 kW	Tj=12°C	COPd	9.45
Tj=bivalent temperature	Pdh	4.51 kW	Tj=bivalent temperature	COPd	3.61
Tj=granična radna temperatura	Pdh	0.90 kW	Tj=granična radna temperatura	COPd	1.06
Bivalentna temperatura		-7 °C			
Granične radne temperature		-27 °C			

Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.007	kW	Cooling	QCE	264	kWh/a
Stanje mirovanja	Psb	0.007	kW	Heating/Average	QHE/A	1294	kWh/a
Stanje isključenosti termostata	Pto	0.057	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Radni medij

Tip				R32			
Težina				1.90	kg		
Potencijal globalnog zatopljenja	GWP			675	kgCO ₂ eq.		

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAV-GP801AT-E	63	65	RAV-GP801AT-E	3180	3180
RAV-GM801UT-E	56	56	RAV-GM801UT-E	1920	1920

Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GP801AT-E	1050 mm	1010 mm	370 mm	74 kg
RAV-GM801UT-E	319 mm	840 mm	840 mm	25 kg

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:
Toshiba Carrier UK Ltd.
Porsham Close, Belliver Industrial Estate,
PLYMOUTH, Devon, PL6 7DB.
United Kingdom