

Split klima uređaj

Outdoor unit	Single inverter	RAV-GP561ATP-E
Indoor unit	4-way Cassette	RAV-RM561UTP-E

Function

Cooling	Y
Grijanje - u prosjeku	Y
Grijanje - toplije	N
Grijanje - hladnije	N

Design load

Cooling	Pdesignc	5.0	kW
Heating/Average	Pdesignh	3.8	kW

Upravljanje kapacitetom = Varijabilno

Seasonal efficiency

Cooling	SEER	7.61	A++
Heating/Average	SCOP(A)	4.96	A++

Cooling

Capacity

Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

Učinkovitost

Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

Tj=35°C	Pdc	5.00	kW	Tj=35°C	EERd	4.10
Tj=30°C	Pdc	3.68	kW	Tj=30°C	EERd	5.82
Tj=25°C	Pdc	2.37	kW	Tj=25°C	EERd	10.00
Tj=20°C	Pdc	1.05	kW	Tj=20°C	EERd	14.61

Grijanje (prosječna klimatska zona)

Capacity

Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.

Učinkovitost

Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.

Tj=-7°C	Pdh	3.36	kW	Tj=-7°C	COPd	3.27
Tj=2°C	Pdh	2.05	kW	Tj=2°C	COPd	4.81
Tj=7°C	Pdh	1.32	kW	Tj=7°C	COPd	6.55
Tj=12°C	Pdh	0.58	kW	Tj=12°C	COPd	7.91
Tj=bivalent temperature	Pdh	3.36	kW	Tj=bivalent temperature	COPd	3.27
Tj=granična radna temperatura	Pdh	0.67	kW	Tj=granična radna temperatura	COPd	0.96
Bivalentna temperatura		-7	°C			
Granične radne temperature		-27	°C			

Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.009	kW	Cooling	QCE	230	kWh/a
Stanje mirovanja	Psb	0.009	kW	Heating/Average	QHE/A	1071	kWh/a
Stanje isključenosti termostata	Pto	0.026	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Radni medij

Tip	R32		
Težina	1.35 kg		
Potencijal globalnog zatopljenja	GWP	675 kgCO ₂ eq.	

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAV-GP561ATP-E	63	65	RAV-GP561ATP-E	2250	2070
RAV-RM561UTP-E	47	47	RAV-RM561UTP-E	1050	1050

Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GP561ATP-E	630 mm	799 mm	299 mm	45 kg
RAV-RM561UTP-E	256 mm	840 mm	840 mm	20 kg

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:
Toshiba Carrier UK Ltd.
Porsham Close, Belliver Industrial Estate,
PLYMOUTH, Devon, PL6 7DB.
United Kingdom