

Split klima uređaj

Outdoor unit	Single inverter	RAV-GP561ATP-E
Indoor unit	Standard Duct	RAV-RM561BTP-E

Function		Design load			Seasonal efficiency			
Cooling	Y	Cooling	Pdesignc	5.0 kW	Cooling	SEER	5.60	A+
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	3.8 kW	Heating/Average	SCOP(A)	4.24	A+
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

Cooling

Capacity				Učinkovitost			
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.				Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.			
Tj=35°C	Pdc	5.00	kW	Tj=35°C	EERd		3.29
Tj=30°C	Pdc	3.68	kW	Tj=30°C	EERd		4.82
Tj=25°C	Pdc	2.37	kW	Tj=25°C	EERd		6.77
Tj=20°C	Pdc	1.05	kW	Tj=20°C	EERd		9.70

Grijanje (prosječna klimatska zona)

Capacity				Učinkovitost			
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.			
Tj=-7°C	Pdh	3.36	kW	Tj=-7°C	COPd		2.80
Tj=2°C	Pdh	2.05	kW	Tj=2°C	COPd		4.21
Tj=7°C	Pdh	1.32	kW	Tj=7°C	COPd		5.45
Tj=12°C	Pdh	0.58	kW	Tj=12°C	COPd		6.36
Tj=bivalent temperature	Pdh	3.36	kW	Tj=bivalent temperature	COPd		2.80
Tj=granična radna temperatura	Pdh	0.67	kW	Tj=granična radna temperatura	COPd		0.82
Bivalentna temperatura		-7	°C				
Granične radne temperature		-27	°C				

Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.009	kW	Cooling	QCE	312	kWh/a
Stanje mirovanja	Psb	0.009	kW	Heating/Average	QHE/A	1254	kWh/a
Stanje isključenosti termostata	Pto	0.060	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Radni medij

Tip	R32		
Težina	1.35 kg		
Potencijal globalnog zatopljenja	GWP	675 kgCO ₂ eq.	

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAV-GP561ATP-E	63	65	RAV-GP561ATP-E	2250	2070
RAV-RM561BTP-E	48	48	RAV-RM561BTP-E	800	800

Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GP561ATP-E	630 mm	799 mm	299 mm	45 kg
RAV-RM561BTP-E	275 mm	700 mm	750 mm	23 kg

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:
Toshiba Carrier UK Ltd.
Porsham Close, Belliver Industrial Estate,
PLYMOUTH, Devon, PL6 7DB.
United Kingdom