

Split klima uređaj

Outdoor unit	Single inverter	RAV-GP561ATP-E
Indoor unit	Ceiling	RAV-RM561CTP-E

Function

Design load

Seasonal efficiency

Cooling	Y	Cooling	Pdesignc	5.0 kW	Cooling	SEER	6.76	A++
Grijanje - u prosjeku	Y	Heating/Average	Pdesignh	3.8 kW	Heating/Average	SCOP(A)	4.70	A++
Grijanje - toplije	N	Upravljanje kapacitetom = Varijabilno						
Grijanje - hladnije	N							

Cooling

Capacity				Učinkovitost			
Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.				Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.			
Tj=35°C	Pdc	5.00 kW		Tj=35°C	EERd		3.65
Tj=30°C	Pdc	3.68 kW		Tj=30°C	EERd		5.43
Tj=25°C	Pdc	2.37 kW		Tj=25°C	EERd		8.41
Tj=20°C	Pdc	1.05 kW		Tj=20°C	EERd		11.78

Grijanje (prosječna klimatska zona)

Capacity				Učinkovitost			
Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.			
Tj=-7°C	Pdh	3.36 kW		Tj=-7°C	COPd		3.13
Tj=2°C	Pdh	2.05 kW		Tj=2°C	COPd		4.63
Tj=7°C	Pdh	1.32 kW		Tj=7°C	COPd		6.03
Tj=12°C	Pdh	0.58 kW		Tj=12°C	COPd		7.25
Tj=bivalent temperature	Pdh	3.36 kW		Tj=bivalent temperature	COPd		3.13
Tj=granična radna temperatura	Pdh	0.67 kW		Tj=granična radna temperatura	COPd		0.92
Bivalentna temperatura		-7 °C					
Granične radne temperature		-27 °C					

Electricity

Electric power input in power modes other than "on mode"

Sezonska snaga električnog priključka

Stanje isključenosti	Poff	0.007	kW	Cooling	QCE	259	kWh/a
Stanje mirovanja	Psb	0.007	kW	Heating/Average	QHE/A	1130	kWh/a
Stanje isključenosti termostata	Pto	0.034	kW	Heating/Warmer	QHE/B	x	kWh/a
Način rada s grijačem kućišta	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Radni medij

Tip	R32		
Težina	1.35 kg		
Potencijal globalnog zatopljenja	GWP	675 kgCO ₂ eq.	

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAV-GP561ATP-E	63	65	RAV-GP561ATP-E	2250	2070
RAV-RM561CTP-E	52	52	RAV-RM561CTP-E	900	900

Dimenzije

	Visina	Širina	Dubina	Težina
RAV-GP561ATP-E	630 mm	799 mm	299 mm	45 kg
RAV-RM561CTP-E	235 mm	952 mm	690 mm	23 kg

Harmonizirana norma EN14511:2007 , EN12102

Metode obračuna - mjerne norme PrEN 14825: 2011 Sekcija 8 i 9

Kontakt partner za dobivanje više informacija

Uvoznik / distributer u EU:
Toshiba Carrier UK Ltd.
Porsham Close, Belliver Industrial Estate,
PLYMOUTH, Devon, PL6 7DB.
United Kingdom