		Р	RODUCT	INFORMATION (*)			
	INDOOR MO	DEL		MOZ FEOGNOW (MOZ FEOGNOO	/MOZ EFOEWOR		
ROOM AIR CONDITIONER	INDOOR MOI			MSZ-EF25VGW / MSZ-EF25VGS	/ MSZ-EF25VGB		
	OUTDOOR M	IODEL		MUZ-EF25VG			
				If function includes heating: I	ndicate the heatin	g season the	
				information relates to. Indicate	ted values should	relate to one	heating
Function (indicate if present)				season at a time. Include at	east the heating s	eason 'Avera	ge'.
				Average (mandatory)		Υ	
cooling		Υ		Warmer (if designated)		Υ	
neating		Υ		Colder (if designated)		N	
				-	•		
tem	symbol	value	unit	Item	symbol	value	un
Design load				Seasonal efficiency			
cooling	Pdesignc	2.5	kW	cooling	SEER	9.1	-
eating/Average	Pdesignh	2.4	kW	heating/Average	SCOP/A	4.7	-
eating/Warmer	Pdesignh	1.3	kW	heating/Warmer	SCOP/W	5.8	
eating/Colder	Pdesignh	х	kW	heating/Colder	SCOP/C	х	-
				_			
Declared cEFacity for cooling	g, at indoor temper	ature 27(19)°	C and	Declared energy efficiency ra	atio, at indoor temp	perature 27(19	9) °C a
outdoor temperature Tj				outdoor temperature Tj			
Гј=35℃	Pdc	2.5	kW	Tj=35°C	EERd	4.7	
Гј=30°С	Pdc	1.9	kW	Tj=30°C	EERd	7.6	
Гj=25°С	Pdc	1.2	kW	Tj=25°C	EERd	10.5	
Гj=20°С	Pdc	8.0	kW	Tj=20°C	EERd	15.2	
Declared cEFacity for heatin		, at indoor ten	nperature	Declared coefficient of perfor	_	eason, at indo	oor
20°C and outdoor temperatur		1		temperature 20°C and outdoo			
Гј=-7°С	Pdh	2.2	kW	Tj=-7°C	COPd	2.8	-
Γj=2°C	Pdh	1.3	kW	Tj=2°C	COPd	4.8	
j=7°C	Pdh	0.8	kW	Tj=7°C	COPd	6.2	
_j=12°C	Pdh	0.6	kW	Tj=12°C	COPd	6.7	
j=bivalent temperature	Pdh	2.4	kW	Tj=bivalent temperature	COPd	2.5	
j=operating limit	Pdh	2.0	kW	Tj=operating limit	COPd	2.2	
				_			
eclared cEFacity for heatin	•	at indoor ten	nperature	Declared coefficient of perfor		eason, at indo	or
				temperature 20°C and outdoo			
•	Pdh	1.3	kW	Tj=2°C	COPd	4.8	
j=2°C			kW	Tj=7°C	COPd	6.2	-
j=2°C	Pdh	0.8	KVV	.,			
Гj=2°С Гj=7°С	Pdh Pdh	0.8	kW	Tj=12°C	COPd	6.7	_
<mark>20°Cand outdoor temperatur</mark> Tj=2°C Tj=7°C Tj=12°C Tj=bivalent temperature				- L		6.7 4.8	-

eclared cEFacity for heating	g/Warmer season, a	at indoor ten	nperature	Declared coefficient of performance/Warmer season, at indoor						
°Cand outdoor temperature	· Tj			temperature 20°C and outdoor temperature Tj						
=2°C	Pdh	1.3	kW	Tj=2°C	COPd	4.8	-			
=7°C	Pdh	0.8	kW	Tj=7°C	COPd	6.2	-			
=12°C	Pdh	0.6	kW	Tj=12°C	COPd	6.7	-			
=bivalent temperature	Pdh	1.3	kW	Tj=bivalent temperature	COPd	4.8	-			
operating limit	Pdh	2.0	kW	Tj=operating limit	COPd	2.2	-			
alared aFFacity for booting	/Colder assess at	indoor tomr	oroturo	Dealared coefficient of performance/Colder access, at indeer						

Declared cEFacity for heatin 20°Cand outdoor temperatur	•	, at indoor temp	perature	Declared coefficient of performance temperature 20°C and outdoor			r
Tj=-7°C	Pdh	х	kW	Tj=-7°C	COPd	х	-
Tj=2°C	Pdh	х	kW	Tj=2°C	COPd	х	-
Tj=7°C	Pdh	x	kW	Tj=7°C	COPd	х	-
Tj=12°C	Pdh	х	kW	Tj=12°C	COPd	х	-
Tj=bivalent temperature	Pdh	х	kW	Tj=bivalent temperature	COPd	х	-
Tj=operating limit	Pdh	х	kW	Tj=operating limit	COPd	х	-
Tj=-15°C	Pdh	х	kW	Tj=-15°C	COPd	х	-
Bivalent temperature				Operating limit temperature			
heating/Average	Tbiv	-10	°C	heating/Average	Tol	-15	°C
heating/Warmer	Tbiv	2	°C	heating/Warmer	Tol	-15	°C
heating/Colder	Tbiv	х	°C	heating/Colder	Tol	х	°C

valent temperature					Operating limit temperature			
eating/Average	Tbiv	-10	°C		heating/Average	Tol	-15	°C
eating/Warmer	Tbiv	2	°C		heating/Warmer	Tol	-15	°C
eating/Colder	Tbiv	Х	°C		heating/Colder	Tol	х	°C

Cycling interval cEFacity				Cycling interval efficiency			
for cooling	Pcycc	х	kW	for cooling	EERcyc	х	Γ
for heating	Pcych	х	kW	for heating	COPcyc	х	
Degradation co-efficient cooling	Cdc	0.25	-	Degradion co-efficient heating	Cdh	0.25	Γ

Electric power input in power m	odes other than 'a	ctive mode	e'	Annual electricity consump	otion	
off mode	P _{OFF}	1	W	cooling	Q _{CE}	96
standby mode	P _{SB}	1	W	heating/Average	Q _{HE}	713
thermostat - off mode	P _{TO}	8	W	heating/Warmer	Q _{HE}	311
crankcase heater mode	P _{CK}	0	W	heating/Colder	Q_{HE}	х

CEFacity control (indicate one of three options)		Other items					
fixed	N	Sound power level (indoor/outdoor)	L _{WA}	60/58	dB(A)		
staged	Z	Global warming potential	GWP	550	kgCO₂eq.		
variable	Y	Rated air flow (indoor/outdoor)	-	630/1668	m³/h		

kWh/a kWh/a kWh/a kWh/a

Contact details for obtaining	Name and address of the manufacturer or of its authorized representative.
more information	The same data does of the managed of or on the data of the special representative.