

PRODUCT INFORMATION (*)

ROOM AIR CONDITIONER	INDOOR MODEL	MSZ-EF50VGW / MSZ-EF50VGS / MSZ-EF50VGB
	OUTDOOR MODEL	MUZ-EF50VG

Function (indicate if present)	
cooling	Y
heating	Y

If function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season 'Average'.	
Average (mandatory)	Y
Warmer (if designated)	Y
Colder (if designated)	N

Item	symbol	value	unit
Design load			
cooling	P _{designc}	5.0	kW
heating/Average	P _{designh}	4.2	kW
heating/Warmer	P _{designh}	2.3	kW
heating/Colder	P _{designh}	x	kW

Item	symbol	value	unit
Seasonal efficiency			
cooling	SEER	7.5	-
heating/Average	SCOP/A	4.5	-
heating/Warmer	SCOP/W	5.4	-
heating/Colder	SCOP/C	x	-

Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature T _j			
T _j =35°C	P _{dc}	5.0	kW
T _j =30°C	P _{dc}	3.7	kW
T _j =25°C	P _{dc}	2.4	kW
T _j =20°C	P _{dc}	1.6	kW

Declared energy efficiency ratio, at indoor temperature 27(19) °C and outdoor temperature T _j			
T _j =35°C	EERd	3.3	-
T _j =30°C	EERd	5.3	-
T _j =25°C	EERd	8.5	-
T _j =20°C	EERd	16.5	-

Declared capacity for heating/Average season, at indoor temperature 20°C and outdoor temperature T _j			
T _j =-7°C	P _{dh}	3.8	kW
T _j =2°C	P _{dh}	2.3	kW
T _j =7°C	P _{dh}	1.4	kW
T _j =12°C	P _{dh}	0.7	kW
T _j =bivalent temperature	P _{dh}	4.2	kW
T _j =operating limit	P _{dh}	3.5	kW

Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature T _j			
T _j =-7°C	COPd	2.8	-
T _j =2°C	COPd	4.6	-
T _j =7°C	COPd	5.8	-
T _j =12°C	COPd	5.4	-
T _j =bivalent temperature	COPd	2.5	-
T _j =operating limit	COPd	1.9	-

Declared capacity for heating/Warmer season, at indoor temperature 20°C and outdoor temperature T _j			
T _j =2°C	P _{dh}	2.3	kW
T _j =7°C	P _{dh}	1.4	kW
T _j =12°C	P _{dh}	0.7	kW
T _j =bivalent temperature	P _{dh}	2.3	kW
T _j =operating limit	P _{dh}	3.5	kW

Declared coefficient of performance/Warmer season, at indoor temperature 20°C and outdoor temperature T _j			
T _j =2°C	COPd	4.6	-
T _j =7°C	COPd	5.8	-
T _j =12°C	COPd	5.4	-
T _j =bivalent temperature	COPd	4.6	-
T _j =operating limit	COPd	1.9	-

Declared capacity for heating/Colder season, at indoor temperature 20°C and outdoor temperature T _j			
T _j =-7°C	P _{dh}	x	kW
T _j =2°C	P _{dh}	x	kW
T _j =7°C	P _{dh}	x	kW
T _j =12°C	P _{dh}	x	kW
T _j =bivalent temperature	P _{dh}	x	kW
T _j =operating limit	P _{dh}	x	kW
T _j =-15°C	P _{dh}	x	kW

Declared coefficient of performance/Colder season, at indoor temperature 20°C and outdoor temperature T _j			
T _j =-7°C	COPd	x	-
T _j =2°C	COPd	x	-
T _j =7°C	COPd	x	-
T _j =12°C	COPd	x	-
T _j =bivalent temperature	COPd	x	-
T _j =operating limit	COPd	x	-
T _j =-15°C	COPd	x	-

Bivalent temperature			
heating/Average	T _{biv}	-10	°C
heating/Warmer	T _{biv}	2	°C
heating/Colder	T _{biv}	x	°C

Operating limit temperature			
heating/Average	T _{ol}	-15	°C
heating/Warmer	T _{ol}	-15	°C
heating/Colder	T _{ol}	x	°C

Cycling interval capacity			
for cooling	P _{cycc}	x	kW
for heating	P _{cyh}	x	kW
Degradation co-efficient cooling	C _{dc}	0.25	-

Cycling interval efficiency			
for cooling	EER _{cycc}	x	-
for heating	COP _{cyh}	x	-
Degradation co-efficient heating	C _{dh}	0.25	-

Electric power input in power modes other than 'active mode'			
off mode	P _{OFF}	1	W
standby mode	P _{SB}	1	W
thermostat - off mode	P _{TO}	8	W
crankcase heater mode	P _{CK}	0	W

Annual electricity consumption			
cooling	Q _{CE}	233	kWh/a
heating/Average	Q _{HE}	1304	kWh/a
heating/Warmer	Q _{HE}	595	kWh/a
heating/Colder	Q _{HE}	x	kWh/a

Capacity control (indicate one of three options)	
fixed	N
staged	N
variable	Y

Other items			
Sound power level (indoor/outdoor)	L _{WA}	60/65	dB(A)
Global warming potential	GWP	550	kgCO ₂ eq.
Rated air flow (indoor/outdoor)	-	678/2412	m ³ /h

Contact details for obtaining more information	Name and address of the manufacturer or of its authorized representative.
--	---

(*) This information is based on the "product information requirement" in COMMISSION REGULATION (EU) No206/2012.